

UNDERLAY SPECIFICATIONS



For wood and laminate floors

Excellent performance on all subfloors



















The Roberts 2.5mm Underlay is simple to install and comes in a convenient fan-fold format with excellent sound absorption, floor levelling and thermal insulation properties. Designed for use with wood and laminate flooring, it's especially suited for high-traffic areas and is an ideal choice for underfloor heating. Made from up to 100% recycled plastics.

Technical Data/Product	Unit	2.5mm Underlay
SKU Code		R02FF
Finish	-	Fan-fold
Dimension	mm	400 x 1200
Pack Size/Folds per Pack	-	26 Boards
Pack Coverage	m²	12.4
Thickness	mm	2.5
Colour	-	Black
Compression Strength	kPa	≥ 150
Compression Creep	kPa	≥ 25
Dynamic Load (DL ₂₅)	Cycles	≥ 250.000
Impact Sound Reduction	dB	= 19
Punctual Conformability (PC Value)	mm	≥ 2.6
Resistance to Large Ball (RLB)	mm	≥ 1400
Water Vapour Permeability (SD Value)	m	-
Thermal Resistance (R Value)	m²K/w	0.06
Tog Rating	Tog	0.6
Water Absorption	Vol. %	< 0.1
Fire Protection Classification	Euroclass	E







A division o



